

DRIVE TRANSMISSION DEVICE AND OPTICAL APPARATUS USING SAME

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] This invention relates to a drive transmission device, a lens unit using the drive transmission device, an optical apparatus that includes an imaging unit, to which the lens unit is detachably mounted, and an optical-apparatus driving unit that is mounted to the lens unit using the drive transmission device.

2. Description of the Related Art

[0002] Fig. 9 shows the structure of a manually-operated part and an electrically-operated system of a conventional optical apparatus, such as that used for television shooting.

[0003] An operating ring 103 is rotatably disposed on the outer periphery of an apparatus body 101. An optical adjusting means, such as a movable lens group, not shown, that is disposed inside the apparatus body 101 can be driven by manual operation of the operating ring 103 or by electric operation from a drive unit mounted in the apparatus body 101.

[0004] A motor 105 and a control circuit used to electrically drive the operating ring 103 are housed in the drive unit. The motor 105 can be activated by operating an electric operation switch, or the like, that is disposed on

09500250 11004

[0005] In the optical apparatus capable of manually and electrically driving the movable lens group, switching between manual drive and electric drive is carried out in most cases by manually operating a clutch mechanism provided with a switching lever.

[0006] In this clutch mechanism, an idler gear 123 slidable in the axial direction of a shaft 124 by the operation of the switching lever, not shown, is provided between an operating gear 104 formed on the operating ring 103 and an output gear 122 of the motor 105.

[0007] When electrically driven, the idler gear 123 is slid by the manual operation of the switching lever to a position where the idler gear 123 is engaged with the operating gear 104 and with the output gear 122, thereby transmitting the driving force of the motor 105 to the operating ring 103 through the idler gear 123.

[0008] When manually driven, the idler gear 123 is slid by the manual operation of the switching lever to a position where the idler gear 123 is disengaged from the output gear 122.

[0009] The switching between manual drive and electric drive is conventionally carried out such that a driving-force transmission path from the motor 105 to the operating

[0010] However, in the optical apparatus in which the transmission path of motor power is turned on or off by operating the switching lever so as to achieve the switching between manual drive and electric drive as described above, the switching lever must be operated whenever the switching therebetween is carried out. Therefore, there is a problem in that operations become complex, and thus quick switching between manual drive and electric drive is made difficult.

[0012] However, a problem resides in that an impulse sound occurs at this time because the idler gear 123 collides with the stopper 126 owing to the urging force of the spring 125.

[0016] Fig. 8 shows the inner structure of the electromagnetic clutch. (a) of Fig. 8 shows the electromagnetic clutch in which the electricity supply to a coil 217 is in an off-state. At this time, an armature 215 connected to the operating ring 103 through a gear train, not shown, is drawn by the urging force of a leaf spring 222 in a direction opposite to a rotor 214 to which a driving force is input from a motor not shown so that the frictional surface 216 of the rotor 214 and the frictional surface 216

of the armature 215 do not come in contact with each other.

[0017] (b) of Fig. 8 shows the electromagnetic clutch in which the electricity supply to the coil 217 is in an on-state. At this time, a magnetic circuit is produced inside the electromagnetic clutch, and the armature 215 is drawn to the rotor 214 against the urging force of the leaf spring 222 and is brought into pressed contact with the rotor 214. Thereafter, engagement torque is generated in the electromagnetic clutch by the frictional force of the frictional surface 216, and the driving force of the motor can be transmitted to the operating ring 103.

[0018] However, if the electromagnetic clutch constructed as shown in Fig. 8 is used, the armature 215 moves in response to the switching between the ON and the OFF of the electricity supply to the coil 217 and collides with the rotor 214 or with the striking surface of the output shaft, and therefore a noise occurs.

[0019] Additionally, an electromagnetic force (i.e., coil voltage) that prevails against the urging force of the spring 222 is required in order for the armature 215 to come in contact with the rotor 214 by attraction. Therefore, delay arises during the period from the start of a command signal for performing the electric drive to the occurrence of the engagement torque resulting from the attractive contact of the armature 215 with the rotor 214.

00000250 111004

[0020] Additionally, the coil voltage required to cause the armature 215 to come in contact with the rotor 214 by attraction is inconstant because, for example, of the individual differences of the electromagnetic clutch.

SUMMARY OF THE INVENTION

[0021] It is therefore an object of the present invention to provide a drive transmission device capable of preventing a sound from occurring when switched between the ON and OFF of the electricity supply, and capable of eliminating delay caused during the period from the beginning of the electricity supply to the engagement between an input member and an output member.

[0022] It is another object of the present invention to provide an optical apparatus or an optical-apparatus driving unit capable of easily, promptly, and quietly performing the switching between manual drive and electric drive by use of the aforementioned drive transmission device, and capable of smoothly performing the manual drive while being electrically driven.

[0023] In order to achieve the objects, according to the present invention, a drive transmission device for transmitting the drive of an actuator to a driven member comprises an input member which is driven by the actuator, an output member for transmitting the drive of the input

09000000-11001

[0024] Further, according to the present invention, an optical apparatus includes a drive transmission device for transmitting drive so as to manually drive an optical member by manually operating a manual-drive member and so as to electrically drive the optical member by transmitting electric drive from an actuator to the manual-drive member. The optical apparatus comprises an optical unit which movably supports the optical member driven by the manual-drive member, an input member driven by the actuator, an output member for transmitting the drive of the input member and driving the manual-drive member, and a state switching unit for performing switching between a first state to transmit drive and a second state so as not to transmit drive in the input member and the output member, in which the input member and the output member are in contact with each other when the state switching unit is in the first state and in the second state.

[0025] Further, according to the present invention, an

[0026] Further, according to the present invention, an optical apparatus includes a drive transmission device for transmitting drive so as to manually drive an optical member by manually operating a manual-drive member and so as to

[0027] Further, according to the present invention, an optical-apparatus driving unit mounted or connected to a body of an optical apparatus including an optical member includes a drive transmission device in which the optical

member can be manually operated by manual operation input to a manual-drive member and in which the optical member can be electrically driven by transmitting electric drive from an actuator to the manual-drive member. The optical-apparatus driving unit comprises an input member driven by the actuator; an output member for transmitting the drive of the input member and driving the manual-drive member; a state switching unit for performing switching between a first state to transmit drive and a second state so as not to transmit drive in the input member and the output member; a command unit for commanding the optical member to be electrically driven, which outputs command information in accordance with operation of a command operating member to the actuator; and a controller for controlling the state switching unit in accordance with the command information from the command unit; in which the input member and the output member are in contact with each other when the state switching unit is in the first state and in the second state.

Further objects and structures of the present invention will become apparent from description of embodiments provided later.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] Fig. 1 is a schematic view showing the structure of a zoom lens body and a drive unit according to a first

0000000000 1111111111

(First embodiment)

Fig. 1 shows the structure of a zoom lens provided with an electromagnetic clutch, which is a drive transmission device according to an embodiment of the present invention. The zoom lens is composed of a zoom lens body 1 and a drive unit (optical-apparatus driving unit) 2 mounted or connected to the zoom lens body 1. The zoom lens body 1 and the drive unit 2 are united with each other through an idler gear 8.

[0038] The zoom lens is replaceably mounted to a television camera 30 and constitutes a camera system, which is an optical apparatus. The zoom lens forms a subject image on an image pickup device 28, for example, of a charge-coupled device (CCD) disposed in the camera 30.

[0039] The drive unit 2 includes an electric operation member 12 serving as a seesaw switch capable of being operated both in a plus direction and in a minus direction based on a predetermined position (i.e., midpoint). The electric operation member 12 outputs a command signal, which is command information, in accordance with the operation of the electric operation member 12. The output of the command signal is then input to a CPU 9.

[0040] A demand (not shown), which is an external operation device, can be connected to the drive unit 2 through a connector (not shown), and a command signal from an electric operation member disposed in the demand can be input to the CPU 9 through the connector.

[0044] The rotor 14 and the armature 15 are made of iron or the like. A friction material 18 used also as a non-magnetic material is embedded in the rotor 14 like a ring. The rotor 14 and the armature 15 are assembled so that their

contact surfaces 16 do not make a gap therebetween, i.e., so that they come in contact with each other.

[0045] When an electric current is passed through the coil 17, a magnetic circuit is produced in the electromagnetic clutch 6, and an attracting force acts between the armature 15 and the rotor 14. As a result, the contact surfaces 16 of the armature 15 and the rotor 14 are pressed against each other, and the rotor 14 and the armature 15 can be rotated together by the frictional force occurring on the contact surfaces 16.

[0046] When an electric current is not passed through the coil 17, an attracting force does not act between the rotor 14 and the armature 15, and therefore the contact surfaces 16 of the rotor 14 and the armature 15 are in contact with each other with such a pressure so as not to bring about drive transmission.

[0047] Thus, in the electromagnetic clutch 6 according to this embodiment, the rotor 14 and the armature 15 are in contact with each other regardless of whether an electric current is passed through the coil 17 or not. Therefore, since the armature 15 never moves when switching between the ON and OFF of the current supply is performed, sounds are prevented from occurring.

[0048] In the conventional electromagnetic clutch constructed as shown in Fig. 8 described above, the armature

[0049] By contrast, in the electromagnetic clutch 6 according to this embodiment, the contact surfaces 16 of the rotor 14 and the armature 15 are always in contact with each other, and a member like a spring by which the armature 15 is separated from the rotor 14 is unnecessary. Therefore, engagement torque is generated even when a voltage supplied to the electromagnetic clutch 6 is low. Therefore, the engagement torque can be smoothly controlled at a wide range.

[0051] Accordingly, the rotor 14 and the armature 15 are attracted and pressed to each other in the electromagnetic clutch 6, and, when the motor 5 is driven, the driving force of the motor 5 is transmitted to the output shaft 20 through

[0052] Although the rotor 14 is used as an input member, and the armature 15 is used as an output member in this embodiment, the rotor 14 may be used as an output member, and the armature 15 may be used as an input member.

[0054] The electric-operation judging part 9a determines whether it is electric drive or manual drive in accordance with the output value of the command signal from the electric operation member 12.

[0055] Fig. 4 shows a change in the output value of a command signal from the electric operation member 12. The output value of the command signal from the electric

operation member 12 changes according to the amount of operation of the electric operation member 12 as shown in the figure. In more detail, a command signal with a reference output value V_0 is output when the electric operation member 12 is not operated. A part where the output value does not change according to a small amount of operation is provided in the intermediate area between the plus side and the minus side with the operational center point of the electric operation member 12 therebetween. This part between V_2 and V_1 centering the reference output value V_0 is a dead zone where the motor 5 does not work owing to the minimum starting voltage of the motor 5 or the load of the lens.

[0056] When the output value of the command signal is between V_2 and V_1 , the electric-operation judging part 9a determines that it is manual drive. When the output value of the command signal is less than V_2 or more than V_1 , the electric-operation judging part 9a determines that it is electric drive.

[0057] The command signal from the electric operation member 12 is also input to the engagement torque calculating part 9b of the CPU 9. The engagement torque calculating part 9b calculates engagement torque (i.e., transmitting force) needed by the electromagnetic clutch 6, and outputs a coil voltage necessary to generate engagement torque

corresponding thereto from the clutch control circuit 10 to the electromagnetic clutch 6.

[0058] When judging that it is electric drive, the electric-operation judging part 9a outputs a motor-driving voltage, which corresponds to the output value of the command signal from the electric operation member 12, to the motor 5 through the motor driving circuit 11, and activates the motor 5.

[0059] At this time, the electromagnetic clutch 6 is engaged by the engagement torque corresponding to the output from the engagement torque calculating part 9b, and the rotation of the motor 5 is transmitted to the zoom lens optical system 1a through the zoom driving ring 3.

[0060] On the other hand, when judging that it is manual drive, the electric-operation judging part 9a stops outputting to the motor 5, and commands the engagement torque calculating part 9b not to supply an electric current to the electromagnetic clutch 6. Thereby, the electromagnetic clutch 6 reaches a state of non-current supply, and the contact surfaces 16 of the rotor 14 and the armature 15 are brought into such contact with each other so as not to generate engagement torque. In this state, the zoom driving ring 29 can be manually operated.

[0061] In this structure, referring to the flowchart of Fig. 5, a description will be provided of operations of the

00550250 444004

CPU 9 in a case where the electric operation member 12 is not operated (or the member 12 is operated within the range of the dead zone).

[0062] First, the output value (Vs) of a command signal from the electric operation member 12 is taken into the electric-operation judging part 9a at step 101.

[0063] Subsequently, a judgment is made as to whether the relation $V1 > Vs > V2$ concerning the command signal Vs is established or not at step 102. Since the relation $V1 > Vs > V2$ is established as shown in Fig. 4 in this case (i.e., manual drive), the flow is ended as it is.

[0064] At this time, the output value of a command signal from the electric operation member of the demand may also be taken into the electric-operation judging part 9a, and a judgment may be made in the same way as at step 102.

[0065] When judging that it is manual drive, the motor 5 does not work because there is no output to the motor driving circuit 11. When judging that it is manual drive, the engagement torque is set at "0" in the engagement torque calculating part 25b. Therefore, no voltage is supplied to the coil 17 of the electromagnetic clutch 6.

[0066] In other words, in Fig. 2, an electric current is not passed through the coil 17, and therefore no attracting force is generated between the armature 15 and the rotor 14. When the zoom driving ring 3 is manually operated and

00000000 111001

the zoom lens optical system 1a through the zoom driving ring 3 is calculated, based on the output value (Vs) of the command signal, which has already been taken, from the electric operation member 12.

[0071] The driving torque is calculated as follows. The driving torque of a lens under various conditions is pre-measured, and the resulting numerical values are stored in an external or internal memory of the CPU 9 in the form of table data. Alternatively, the measured driving torque is expressed as an approximation formula, and factor data concerning it is stored in the memory. Necessary driving torque corresponding to the output of the electric operation member 12 is then calculated from the memory data by the use of the table data or the approximation formula.

[0072] Thereafter, necessary transmitting torque T_d of the electromagnetic clutch 6 is calculated in accordance with the necessary driving torque T_k at step 104. In detail, the necessary driving torque T_k is multiplied by a safety factor α ($\alpha=1.2$ or 1.4 , for example) with a margin so as to obtain the necessary transmitting torque T_d .

[0073] Thereafter, engagement torque T_d' of the electromagnetic clutch 6 needed to generate the necessary transmitting torque T_d is calculated at step 105. The engagement torque T_d' is obtained from the following equation:

0000050 11004

$$T_d' = T_d / Z_1 / \beta$$

where Z_1 is the reduction gear ratio from the output gear 7 of the electromagnetic clutch 6 to the driving gear 4 of the zoom driving ring 3, and β is transmission efficiency from the output gear 7 to the driving gear 4.

[0074] Subsequently, supplied voltage (V_d) of the electromagnetic clutch 6 onto the coil 17 needed to generate the engagement torque T_d' is calculated, and the resulting voltage is output to the electromagnetic clutch 6 at step 106.

[0075] When the voltage V_d is output to the electromagnetic clutch 6, the coil 17 is treated with the voltage as shown in Fig. 2, and a magnetic circuit is formed in the electromagnetic clutch 6. The armature 15 is then attracted to the rotor 14 owing to an electromagnetic force (attracting force) N generated by the magnetic circuit.

[0076] As a result, the engagement is established with the transmitting force (engagement torque) expressed by the following equation:

$$T_d' = \mu \times N \times r$$

where μ is the friction coefficient between the rotor 14 and the armature 15, and r is an average radius of a contact part between the rotor 14 and the armature 15.

[0077] On the other hand, when judging that it is electric drive, a command signal from the electric operation member

00000000 1111001

[0081] First, the electric operation member 12 is operated, and the zoom ring is electrically driven in the same way as

[0082] After that, the zoom driving ring 3 is manually rotated in the opposite direction against the rotating of the motor 5 while the zoom driving ring 3 is being electrically driven. Thereupon, since a sensor or a similar device is not provided for detecting the manual operation of the zoom driving ring 3, the electric-operation judging part 9a determines that it is a normal electric drive. As a result, the motor 5 is rotated as described above, and the electromagnetic clutch 6 is engaged by necessary engagement torque.

$$T_{sy}' = T_{sy} / Z1 / \beta$$

[0084] On the other hand, since the rotor 14 is connected to the motor 5 through the input shaft 19 and is rotated and driven by the motor 5, the rotor 14 and the armature 15 will be rotated in mutually opposite directions at the contact

[0085] Referring to the torque relationship, generally, $T_m > T_d'$ and $T_d' > T_k'$ as mentioned above. Therefore, the relation $T_m > T_d' > T_k'$ is established where T_m is the maximum torque that the motor 5 can generate by which the rotor 14 is rotated and driven, and T_k' is driving-torque needed to drive the armature 15 that drives the zoom lens optical system 1a through the zoom driving ring 3. Further, since $T_{sy}' > T_d'$, both the rotor 14 and the armature 15 slide on the contact surface 16 of the electromagnetic clutch 6 and are at last rotated in mutually opposite directions.

[0087] Therefore, a comfortable operational feel can be obtained with respect to a case where the electromagnetic clutch 6 is engaged by engagement torque greater than the torque T_m in which the rotor 14 is rotated and driven by the

[0088] Further, since sliding occurs between the armature 15 and the rotor 14, an excessive load can be prevented from being imposed on the motor 5, etc., even when the zoom driving ring 3 or the idler gear 8 suddenly stops because of some trouble while being electrically driven.

[0089] There, a description was given of a case where the zoom driving ring 3 is manually operated in the direction opposite to the electric drive direction. However, the same applies to a case where the zoom driving ring 3 is manually and forcibly stopped while being electrically driven, or a case where the zoom driving ring 3 is manually braked to reduce the zoom speed, or a case where the zoom driving ring 3 is manually accelerated at a speed higher than the electric drive speed in the same direction as the electric drive direction.

(Second embodiment)

In the first embodiment described above, a description was provided of a case where the electromagnetic clutch 6 is brought into a state of non-current supply (i.e., the engagement torque of the electromagnetic clutch 6 is fixed at "0") when the electric-operation judging part 9a determines that it is manual drive. However, the electromagnetic clutch 6 can be brought into a state of

[0091] In more detail, voltage to engage the electromagnetic clutch 6 by engagement torque Td'' ($0 \leq Td'' < Tk' < Td'$) is supplied to the electromagnetic clutch 6 when the electric-operation judging part 9a determines that it is manual drive.

[0092] Thereafter, the zoom driving ring 3 is manually operated and rotated, thereby rotating the armature 15 through the idler gear 8, the output gear 7, and the output shaft 20. At this time, the armature 15 is engaged with the rotor 14 by the engagement torque T_d'' , and the armature 15 is rotated while sliding on the rotor 14.

[0093] As a result, torque needed to manually operate the zoom driving ring 3 increases by an amount proportional to the engagement torque T_d ". Therefore, it is possible to load the manual operation of the zoom driving ring 3 to some degree, and to give an excellent manual operational feel to a cameraman who likes some load added to the manual operation.

[0094] Additionally, if the engagement torque T_d of the electromagnetic clutch 6 can be changed with the volume 13 which is an adjusting member, the load given when the zoom driving ring 3 is manually operated can be set in accordance

[0095] Referring again to the conventional electromagnetic clutch constructed as shown in Fig. 8 described above, since the armature 215 is attracted to the rotor 214 against the force of the leaf spring 222 when electricity is supplied, a certain degree of voltage is needed until the engagement torque is generated, and manual torque needed to drive the zoom driving ring, which includes the engagement torque needed when attracted, suddenly increases when the voltage supplied to the electromagnetic clutch reaches a given value as shown in (b) of Fig. 6.

[0096] By contrast, in the electromagnetic clutch 6 according to this embodiment, since the contact surfaces 16 between the rotor 14 and the armature 15 are designed to be always in contact with each other, manual torque needed to drive the zoom driving ring 3, which includes the engagement torque T_d of the electromagnetic clutch 6, increases proportionately with the voltage supplied to the electromagnetic clutch 6 as shown in (a) of Fig. 6, and the adjustment range of the manual torque is enlarged.

[0097] When the manual torque is adjusted and set, it can be set by an external adjusting device (e.g., personal computer) connectable to the lens apparatus, and not only by an adjusting means, such as the volume 13, mounted in the drive unit.

[0102]

In the electromagnetic clutch 6 of the first and second embodiment, an intermediate member 21, which is made of a material with excellent slidability and constitutes a contact surface with the rotor 14 or with the armature 15, may be attached to the rotor 14 or the armature 15, as shown in Fig. 7. The intermediate member 21 can be made of Teflon or polyethylene, for example.

[0103] Thereby, likewise, even if the rotor 14 and the armature 15 are in contact with each other when no electricity is supplied, or even if they are in pressed contact with each other when electricity is supplied, necessary manual torque acts on the zoom driving ring 3, and the contact surfaces are smoothly slid, thus preventing a sliding sound from occurring, or preventing unsmoothness caused by friction from occurring. As a result, a manual

[0104] In each embodiment, a description was given of the zoom lens in which the drive unit 2 is mounted to the zoom lens body 1. However, the present invention is also applicable to a zoom lens in which a zoom lens body part and a driving system part are integrally contained in an outer casing and are mounted to a camera (however, a member equivalent to the zoom driving ring 3 can be manually operated).

[0106] Further, in each embodiment, a description was given of a case where the electric operation member of the lens or the demand is used as a command means. However, the command means of the present invention is not limited to

[0107] This is effective in another embodiment in which the focus lens unit is manually operated and driven while being electrically driven according to the automatic focus function. In this case, ON/OFF of the electricity supply to the electromagnetic clutch may be switched according to a judgment as to whether or not a command signal has been merely input, not according to a judgment as to whether or not a command signal exceeding a predetermined range has been input as in each embodiment.

[0108] Further, in each embodiment, a description was given of a case where the drive transmission device is applied to the zoom lens. However, the aforementioned drive transmission device can be used for optical apparatuses other than the zoom lens or for various devices other than the optical apparatus.

[0109] As described above, according to the aforementioned embodiments, the input member and the output member of the electromagnetic clutch are in contact with each other not only when an electricity is supplied but also when no

[0110] Further, the input and output members are not separated, for example, by a spring when no electricity is supplied, and therefore it is possible to generate engagement torque within a wide range without delaying from the beginning of the build-up of an electricity supply value when electricity is supplied.

[0112] In this case, the input and output members have slidability because, for example, of the lubricant, and a frictional force occurring on the contact surfaces becomes

[01113] Further, according to the aforementioned embodiments, the input and output members of the electromagnetic clutch, which are used for switching between manual drive and electric drive in the optical apparatus or the optical-apparatus driving unit, are in contact with each other not only when electricity is supplied but also when no electricity is supplied, and therefore it is possible to prevent the generation of a sound caused by the movement of a movable member as an armature of the input and output members when switched between a state of non-electricity supply and a state of electricity supply, and it is possible to promptly and quietly switch between manual drive and electric drive.

[0114] Further, the input and output members are not separated from each other, for example, by a spring when no electricity is supplied to the electromagnetic clutch, and

therefore it is possible to generate engagement torque within a wide range without delaying from the beginning of the build-up of an electricity supply value when electricity is supplied, and it is possible to widely set a manual operational force when the electromagnetic clutch is brought into a state of electricity supply while being manually operated.

[0116] Further, according to the aforementioned embodiments, the electromagnetic clutch is brought into the

—

[0120] Especially, if the electricity supply value for the electromagnetic clutch is controlled to satisfy the relation $0 < T_d < T_k'$, it is possible to soften a shock to the manual operation that occurs from the fact that current electricity supply to the electromagnetic clutch is stopped, so that the

